



suparule



507 Multimeter

- 3¾ digit, 4000 count digital display
- 41 segment analogue bar graph
- Frequency & Capacitance measurement
- Temperature measurement
- THD @ 50/60Hz measurement (optional)

DESCRIPTION

The 507 Multimeter by Finest is a compact auto-ranging DMM, with a number of unique features normally found in more expensive and complex equipment, e.g. Total Harmonic Distortion measurement option, and GO-NO-GO Test Comparator

The Multimeter provides superior quality and features at low cost. As a distributor of Finest products, SupaRule provides prompt services and competitive prices

FEATURES

- Large LCD
- 4000 count display with analog bargraph
- Auto-ranging
- Current Terminals Safety Shutter protection
- Fused 10 Amps range
- True RMS on AC voltage and current ranges
- DC voltage accuracy to 0.3%
- Fix Hold™ (Automatic Reading Hold)
- Capacitance Measurement
- Frequency Measurement
- Temperature Measurement
- Continuity beeper & diode test
- Record, offset & relative modes
- GO-NO-GO Comparison Test facility
- Protective holster and stand

SPECIFICATIONS

Display Count		4000
DC Volt Range		1000V
Accuracy		0.3% + 2d
Resolution		0.1mV
AC Volt Range		750V
Accuracy		0.75% + 3d
Resolution		1mV
DC Amp Range		10A
Accuracy		0.5% + 1d
Resolution		0.1uA
AC Amp Range		10A
Accuracy		1.0% + 1d
Resolution		0.1uA
Ohms Range		40M W
Accuracy		0.5% + 3d
Resolution		0.1 W
Frequency Range		>200KHz
Accuracy		0.05% + 2d
Resolution		0.01Hz
Capacitance Range		1000uF
Accuracy		1.9% + 2d
Resolution		0.001uF
Temperature Range		-40 - +1370 °C
Accuracy		1.0% + 1°C
Resolution		0.1°C
Continuity Beeper		<100 W
Oper. Temp / Humidity		0 - 45 °C / <80%RH
Battery Life		200hrs (alk.)
Dimensions		190 x 85 x 40 mm
Weight		380 g
Safety Standard		CAT III 600V

Distributor:

Suparule Systems Ltd.,
Lonsdale Road,
National Technology Park,
Limerick, Ireland.

Ph.: +353 (0) 61 201030
Fax.: +353 (0) 61 330812
Email: info@suparule.com
Web: www.suparule.com