



suparule



Leica Disto A2

- Measures from 0.05m to 60m
- Measures distance, area, volume
- Robust, shockproof, dustproof

DESCRIPTION

DISTO™ A2 is extremely easy to use and it accurately measures distances, areas and volumes with simple single key operations. DISTO™ A2 is a one-person operated unit, measuring distances from 0.05m to 60m. Measure areas and volumes comfortably and quickly with ± 1.5 millimeter accuracy, even in difficult or unreachable places.

FEATURES

- Accurate Laser Technology
- Simple and fast operation
- Measures distance, areas and volumes
- Min/Max & Continuous measurement mode
- Small, light-weight and easy-to-use
- Designed for indoor measurement
- Backlit multi-line display

APPLICATIONS

The Disto A2 is ideally suitable for construction workers, craftsmen and many other measuring professionals.

SPECIFICATIONS

Measuring Accuracy	Typical: ± 1.5 mm
Range	0.05 m to 60 m
Smallest Unit Displayed	1mm
Ø Laserspot (at distance)	6 / 30 / 60 mm 10 / 50 / 100 m
Units Displayed	Metric/Imperial
Temperature Range	Operating: -10°C to $+50^{\circ}\text{C}$
Degree of Protection	IP50
Dimensions	124x 54x 35 mm
Weight	155g
Battery	Type 9v
Battery Life	Up to 5,000 measurements
Warranty	2 years

Distributor:

Suparule Systems Ltd,
Suparule House,
Lonsdale Road,
National Technology Park,
Limerick, Ireland.

Ph.: +353 (0) 61 201030
Fax.: +353 (0) 61 330812
Email: info@suparule.com
Web: www.suparule.com